

CEN DXB 40 SG-CE

Description

A very performance oil especially designed for diesel engines operating in very difficult conditions and hot climates. It ensures a particularly resistant lubricant film and a high oil pressure in all circumstances thanks to its high and stable viscosity. It is particularly suitable in cases where conventional oil use provokes high oil consumption and excessive wear.

Application

The SUPERB DXB 40+ has been specially designed for Diesel turbo-compressed and atmospheric engines submitted to the worse conditions used engines, tropical climates, poor cooling, operating capacities under very high load and on all types of terrains, in deserts or on mountain roads.

Specification

SAE:40 / 50	CCMC D2and D4
API: CE/SG	ALLISON:C3
MIL - L -2104 E	CATERPILAR TO2
MIL - L -46152 D	

FEATURES AND BENIFITS

- High and stable viscosity ensuring excellent lubricity at high temperatures and severe working conditions.
- Excellent thermal stability and resistance to oxidation.
- Strong detergent and dispersing power ensuring the inner engine cleanliness.
- Good Protection against the acid formation because of the high sulphur content in diesel oil combustion.
- very good anti-wear and anti-corrosion properties.
- Significantly reduces oil consumption.

TYPICAL INSPECTION DATA

SUPERB DXB 40+		400023166
Specific gravity @15 C		0.891
Kinematic Viscosity @40 C	mm/s (cSt)	180
Kinematic Viscosity @100 C	mm/s (cSt)	20
Viscosity index (ASTM D 2270 -79)		130
Flash Point (ASTM D 92)	C	240
Pour point	C	-21
T.B.N (ASTM D 2896-85)	% Weight	13.5
Sulphated ash content (ASTM D 874)	%	1.8