

Century Centurion 15W40 CH-4 HIGH TBN

Description

High Performance lubricant With High TBN for diesel and gasoline engines working in sever conditions.

Applications

Century Centurion 15W40 ch-4 High TBN have been developed for the countries where sulphur content in diesel is above 0.5% (500 ppm). It is recommended for any diesel engine turbocharged or not, for trucks, public work engines, tractors, gen sets, ...It is compatible both with older and newer engines. It is suitable for the most server utilization.

Century Centurion 15W40 CH-4 HIGH TBN is also suitable for gasoline engines to simplify fleets maintenance.

Specifications

API CH-4/SL

Manufacturers Performance level

MB 228.3/229.1 - CAT TO2 - SCANIA ED - MAN SHPD QC - 13017 - VOLVO VDS - MACK EON-L

Features and benefits

HIGH TBN - 20 - to fight against acidity generated by high sulphur content diesel combustion

- Anti wear properties to reduce bore polishing
- Excellent resistance to oxidations and very stable veriosity for a perfect use in all weather conditions
- Excellent anti wear properties to increase engine life

TYPICAL INSPECTION DATA

	UNIT	VALUE
SAE grade		15W40 HIGH TBN
Specific gravity at 15°C	Kg/m ³	880
Kinematic viscosity at 40°C	mm ² /s	115
Kinematic viscosity at 100°C	mm ² /s	16
Flash point	°C	228
Pour point	°C	-30°
TBN	mgKOH/g	12,6