

Century SUPREME 20W50

DEFINITION

Advanced Performance oil for a variety of diesel engine especially for high loaded commercial diesel vehicles

SPECIFICATIONS

Answer to following Specifications

API SJ/SL/CG-4CF-4

ACEA A3/B3/E2

MB p 228.1/MB p 229.1

ALLISON C4

VOLVO VDS-2

DESCRIPTION

Excellent wear resistance even under prolonged stressing full engine load.

Protection against mirror surface formation on cylinder races

Protection against corrosion even when high sulfur content diesel fuels are used

Reliable protection against deposit and sludge during extremely high thermal stress and stop and start driving

APPLICATIONS

long life high performance lubricant designed to meet the demands of the most efficient diesel engines with or without turbocharger in trucks, buses and industrial equipment

CHARACTERISTICS

	UNIT	VALUE	TEST METHOD
SAE grade		20W50	
Specific gravity at 20°C	Kg/m ³	889	NFT 60101
Kinematic viscosity at 40°C	mm ² /s	162.87	NFT 60100
Kinematic viscosity at 100°C	mm ² /s	17.72	NFT 60100
Viscosity index		117	NFT 60136
Flash point	°C	250	NFT 60118
TBN	mg KOH/g	10.8	NFT 60105